



SL-DL22

SULAND COB downlight is unique designed with reflector and COB high power LED chip.
 Low profile heatsink suitable for all kinds of installations.
 Aluminium profile provides excellent thermal dissipation.
 Isolated driver solution both in dimmable and non-dimmable version achieves stable working performance.
 Application: Suitable for commercial and residential applications like office, supermarket, shop, school, hotel, restaurant, workshop, warehouse, home etc.

Model	Voltage	Power	Non-DIM Lumen (±5%)				DIM Lumen (±5%)			
			3000K	4000K	5000K	5700K	3000K	4000K	5000K	5700K
SL-DL22-3-10W	AC100-240V AC200-240V	10W	660	680	750	780	650	670	700	730
SL-DL22-3-13W	AC100-240V AC200-240V	13W	810	820	900	930	790	810	850	880
SL-DL22-4-18W	AC100-240V AC200-240V	18W	1300	1370	1370	1390	1250	1300	1320	1360
SL-DL22-4-25W	AC100-240V AC200-240V	25W	1830	1840	1850	1870	1690	1700	1740	1790
SL-DL22-6-18W	AC100-240V AC200-240V	18W	1310	1370	1380	1390	1260	1320	1330	1370
SL-DL22-6-25W	AC100-240V AC200-240V	25W	1830	1840	1850	1870	1690	1700	1740	1790
SL-DL22-6-35W	AC100-240V AC200-240V	35W	2490	2600	2650	2730	2450	2550	2640	2710
SL-DL22-6-40W	AC100-240V AC200-240V	40W	2950	3010	3200	3300	2710	2770	2950	3030
SL-DL22-8-18W	AC100-240V AC200-240V	18W	1310	1380	1390	1400	1260	1330	1340	1380
SL-DL22-8-25W	AC100-240V AC200-240V	25W	1840	1850	1860	1880	1700	1710	1750	1800
SL-DL22-8-35W	AC100-240V AC200-240V	35W	2500	2620	2670	2750	2460	2560	2660	2720



Model	Dimension(mm)		Product size (mm)	Cut out (mm)	Net weight	Carton size	Q'ty/CTN
	A	B					
SL-DL22-3	110	53	Ø110x53	Ø90-100	0.6kg	39x28x57cm	30pcs
SL-DL22-4	145	65	Ø145x65	Ø120-130	0.85kg	35x33x59cm	20pcs
SL-DL22-6	190	75	Ø190x75	Ø160-170	1.42kg	66x46x27cm	12pcs
SL-DL22-8	225	87	Ø225x87	Ø200-210	1.6kg	53x51x45cm	12pcs