

165W STARLINE LED Lowbay



Product Features:

- Designed by Suland Lighting to optimized warehouse racking luminaire spacing
- Reduced fitting count typically 1 fitting replaces 1.5 conventional luminaires - 40° x 100° beam maximizes luminaire spacing
- **4 in 1** Multi-Purpose Mounting Bracket – Surface Mount, Jack Chain, Solid Rod, Catenary Wire
- Energy efficient LED Lowbay, efficacy of 145lm/W
- Compact and modern design, fitting height only 190mm
- Replaces conventional MV and MH Highbays/ Lowbays - energy savings up to 60%
- Meanwell HBG driver and Lumileds LED chip for greater reliability and longer life
- Integrated heat sink design for better heat dissipation
- Patent wave-shaped linear anti-glare lens for optimum control in direct glare
- Weatherproof design - IP66 rating
- 1.2 metre flex and 3 pin plug standard
- 5 Year Replacement Warranty

Application:

- Industrial factories, workshops and warehouses with vertical racking
- Outdoor canopy light and loading bay lighting
- Linear floodlighting applications



Quick Spec

Luminous Efficacy: 145 lm/W


Color Temperature: 5000K

Color Rendering Index: Ra > 75

Average rated LED life: 60,400hrs @ L70

Ambient Temperature: -35°C to 45°C

Beam Angle: 40° x 100°



| Model | LCP | Supply Voltage | Lumen Output | Dim (mm) | Weight | IP Rating |
|-----------------|--------|----------------|--------------|-----------|--------|-----------|
| SL-BL40100-165W | 162.3W | AC90-305V,50Hz | 23587lm | Ø300*H190 | 4.7kgs | IP66 |